



40 x 26 x 12
2 mm (0,08")

40 x 26 x 12
4 mm (0,16")

50 x 25 x 10
5 mm (0,20")

40 x 26 x 12 2 mm (0,08")			40 x 26 x 12 4 mm (0,16")			50 x 25 x 10 5 mm (0,20")		
NPN	PNP	AC	NPN	PNP	AC	NPN	PNP	AC
-	●/-	●/-	-/●	-/●	-/●	●/-	●/-	-
-	KIB-E40PS/ 002-KL2 650.2984.023 263/1	KIB-E40AS/ 002-L2 650.3584.004 265/4	-	KIN-E40PS/ 004-KL2 650.2984.024 263/1	KIN-E40AS/ 004-L2 650.3584.005 265/4	KIB-E50NS/ 005-KL2 650.2390.001 263/4	KIB-E50PS/ 005-KL2 650.2990.001 263/1	-
-	●/-	●/-	-/●	●/-	●/-	-/●	●/-	-
-	KIB-E40PÖ/ 002-KL2 650.2784.006 263/2	KIB-E40AÖ/ 002-L2 650.3484.003 265/5	-	KIN-E40PÖ/ 004-KL2 650.2784.007 263/2	KIN-E40AÖ/ 004-L2 650.3484.004 265/5	-	-	-
-	-/●	-/●	-/●	-/●	-/●	-	-	-
-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-
-	10-36 V	20-250 V AC	10-36 V	10-36 V	20-250 V AC	10-60 V	10-60 V	-
-	-/200 mA	-/300 mA	-/200 mA	-/200 mA	-/300 mA	-/200 mA	-/200 mA	-
-	800 Hz	10 Hz	400 Hz	400 Hz	10 Hz	500 Hz	500 Hz	-
-	●	-	●	●	-	●	●	-
-	●/-	●/-	●/-	●/-	●/-	●/-	●/-	-
-	-	-	-	-	-	-	-	-
-	-25 °C/+70 °C	-25 °C/+70 °C	-25 °C/+70 °C	-25 °C/+70 °C	-25 °C/+70 °C	-25 °C/+70 °C	-25 °C/+70 °C	-
-	-13 °F/+158 °F	-13 °F/+158 °F	-13 °F/+158 °F	-13 °F/+158 °F	-13 °F/+158 °F	-13 °F/+158 °F	-13 °F/+158 °F	-
-	IP 67/NEMA 4	IP 67/NEMA 4	IP 67/NEMA 4	IP 67/NEMA 4	IP 67/NEMA 4	IP 67/NEMA 4	IP 67/NEMA 4	-
-	PA 6.6	PA 6.6	PA 6.6	PA 6.6	PA 6.6	PA 6.6	PA 6.6	-
-	PVC 3x0,5	PVC 2x0,5	PVC 3x0,5	PVC 3x0,5	PVC 2x0,5	PVC 3x0,5	PVC 3x0,5	-
-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-

