





**41,5 x 41,5 x 120 erhöhter Schaltabstand**  
20 mm (0,78")

**41,5 x 41,5 x 120 erhöhter Schaltabstand**  
40 mm (1,57")

20 mm (0,78")			40 mm (1,57")		
●/-	●/-	-	-/●	-/●	-
NPN	PNP	AC	NPN	PNP	AC
		-			-
KIB-N44DP/ 020-KLSE <b>650.2054.004</b> 263/7 ●/-		-	KIN-N44DP/ 040-KLSE <b>650.2054.005</b> 263/7 ●/-		-
-	-	KIB-N44AP/ 020-LSE <b>650.3554.001</b> 265/6 ●/-	-	-	KIN-N44AP/ 040-LSE <b>650.3554.002</b> 265/6 -/●
-	-	-	-	-	-
-	10-60 V	20-250 V	-	10-60 V	20-250 V
-	-400 mA	-500 mA	-	-400 mA	-500 mA
-	50 Hz	15 Hz	-	50 Hz	15 Hz
-	●	-	-	●	-
-	●/●	●/●	-	●/-	●/●
-	-	-	-	-	-
-	-25 °C/+70 °C	-25 °C/+70 °C	-	-25 °C/+70 °C	-25 °C/+70 °C
-	-13 °F/+158 °F	-13 °F/+158 °F	-	-13 °F/+158 °F	-13 °F/+158 °F
-	IP 65/NEMA 12	IP 65/NEMA 12	-	IP 65/NEMA 12	IP 65/NEMA 12
-	PA 6.6	PA 6.6	-	PA 6.6	PA 6.6
-	-	-	-	-	-
-	-	-	-	-	-
-	-	-	-	-	-

